

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.865 g/cm <sup>3</sup>
Viscosity @ 100°C (cSt)	16.5 cSt
Viscosity @ 40°C	100 cSt
Colour	Brown
Phosphorus (%)	0.05 %
Pour Point (°C)	-39 °C
Calcium (%)	0.29 %

## MVMTF Plus 75W-90

### Fully Synthetic

Recommended by Comma for applications requiring any of the following:

API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90), BMW MTF LT-4, Fiat 9.55550-MZ1, Ford WSD-M2C200-B, Ford WSD-M2C200-C, GM 1940182, GM 1940764, GM 1940768, Nissan MT-XZ Sports & Off-Road Vehicles, Volkswagen G 50, Volvo 97309

#### Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance
- Good low temperature performance
- Excellent cleanliness
- Robust corrosion protection
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

#### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

**UPDATED: 26.06.2025**