



Typical Inspection Data:

| | |
|-------------------------|-------------------------|
| Density @ 20°C | 0.865 g/cm ³ |
| Viscosity @ 100°C (cSt) | 16.5 cSt |
| Viscosity @ 40°C | 100 cSt |
| Colour | Brown |
| Phosphorus (%) | 0.05 % |
| Pour Point (°C) | -39 °C |
| Calcium (%) | 0.29 % |

MVMTF Plus 75W-90

Fully Synthetic

Recommended by Comma for applications requiring any of the following:

API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90), BMW MTF LT-4, Fiat 9.55550-MZ1, Ford WSD-M2C200-B, Ford WSD-M2C200-C, GM 1940182, GM 1940764, GM 1940768, Nissan MT-XZ Sports & Off-Road Vehicles, Volkswagen G 50, Volvo 97309

Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Good low temperature performance.
- Excellent cleanliness.
- Robust corrosion protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 09.04.2026