



Typical Inspection Data:

Colour	Grey/black
Texture	Smooth
NLGI	2 (medium)
Worked Penetration	280
Drop Point	195
Operating Temperature Range	-10 to 120 °C
Oil Separation (168 hours @ 40°C)	<7 %
Copper Corrosion (24 hrs @ 100°C)	1a b
Water Washout @38°C	<7 %
4 ball Weld Load	3600 N

CV Lith-Moly Grease

NLGI 2

Product Features:

- Lithium-based grease, containing molybdenum disulphide. Specially formulated for use in constant velocity joints.
- High in extreme pressure additives to give long life under heavy loads.
- Chemically compatible with polymeric boot material.
- Includes a lamellar solid lubricant which overcomes boundary lubrication.
- Good corrosion protection – Rust inhibited to protect bearing surfaces.

Directions for use:

- Never over pack the bearing
- It is sound lubrication practice to remove the old grease before new grease is introduced. If used grease cannot be removed, Comma CV Lith-Moly grease is generally compatible with other lithium based greases. When mixed with other grease types, this grease should be satisfactory below an operating temperature of 80 °C

Handling:

- Avoid extremes of temperature
- Store under cover
- Product in cardboard cartons must be stored under cover and away from damp conditions
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 09.04.2026