

Technical Data Sheet



Typical Inspections Data:

Density @ 20°C	0.865 g/cm3
Viscosity @ 100°C (cSt)	13.9 cSt
Viscosity @ 40°C (cSt)	93 cSt
Viscosity Index	153
Viscosity CCS @ -25°C	6000 °C
T.B.N (mg KOH/g)	8 mg KOH/g
Sulphated Ash Mass (%)	1.3 %
Zinc (%)	0.11 %
Colour	Brown
Phosphorus (%)	0.1 %
Flash Point (OC)	230 °C
Pour Point (OC)	-36 °C
Calcium (%)	0.24 %

X-FLOW TYPE XS 10W-40

Semi Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA A3/B3, API SL/CF

Directions for use:

- Semi synthetic 10W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 16.04.2024