

# Technical Data Sheet



## Typical Inspection Data:

Density @ 20°C	0.847 g/cm3
Viscosity @ 100°C (cSt)	10.6 cSt
Viscosity @ 40°C	60
Viscosity Index	168
Viscosity CCS @ -30°C (cP)	3900 cP
T.B.N (mg KOH/g)	9.5 mg KOH/g
Sulphated Ash Mass (%)	1.1 %
Zinc (%)	0.11 %
Colour	Brown
Phosphorus (%)	0.11 %
Flash Point (°C)	250 °C
Pour Point (°C)	-36 °C
Calcium (%)	0.26 %

## X-FLOW TYPE F PLUS 5W-30

### Fully Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA A5/B5, API SL/CF, WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C, WSS-M2C913-D

#### Product Features:

- Fully synthetic 5W-30 oil for Ford petrol and diesel engines including Zetec and pre 2009 DuraTec and DuraTorq engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com)

#### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 08.05.2025

Moove Lubricants Ltd. Dering Way, Gravesend, Kent, DA12 2QX, UK

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: [sales@commaoil.com](mailto:sales@commaoil.com) [www.CommaOil.com](http://www.CommaOil.com)