

Technical Data Sheet



Typical Inspection Data: Density @ 20 °C 0.845 g/cm³ Viscosity @ 100 °C 9.7 cSt Viscosity @ 40 °C 50 cSt Viscosity Index 195 Viscosity CCS @ -35 °C 6100 cP T.B.N. 8.0 mg KOH/g **Sulphated Ash Mass** 0.8% Zinc 0.10% Calcium 0.18% **Phosphorus** 0.09% Colour Brown Flash Point >200 °C **Pour Point** -45 °C

Eco-FE Plus 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

Ford WSS-M2C950-A; Jaguar Land Rover STJLR.03.5007; ACEA C2

Product Features:

- Fully synthetic, low-SAPS engine oil specifically developed for latest technology Ford engines from 2014 onwards, new Land Rover and Jaguar models from 2015 and 2016 onwards.
- Designed for high fuel efficiency.
- Suitable for petrol and diesel vehicles.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

10-11-2017