



Typical Inspection Data:

Density @ 20 °C	0.865 g/cm ³
Viscosity @ 100 °C	13.7 cSt
Viscosity @ 40 °C	92 cSt
Viscosity Index	155
Viscosity CCS @ -25 °C	6400 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.11%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

Eurolite 10W-40

Semi Synthetic

Official Approvals:

Approved under VW standard VW 501 01 and
VW 505 00 standard

Recommended by Comma for applications requiring:

RN0700, RN0710;
PSA B71 2300;
MB 229.3;
ACEA A3/B4; API SN CF

Product Features:

- Semi synthetic, high performance 10W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

02-06-2017