

Technical Data Sheet



Typical Inspection Data:	
Density @ 20°C	0.836 g/cm ³
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	38 cSt
Viscosity Index	190
Viscosity CCS @ -35 °C	4400 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8 %
Zinc	0.10%
Calcium	0.18 %
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-45°C

Eco-M 0W-20

Fully Synthetic

Recommended by Comma for applications requiring:

MB 229.71:

Jaguar Land Rover STJLR.51.5122; ACEA C5

Product Features:

- Fully synthetic high performance 0W-20 engine oil
- Maximises engine performance and protection
- Compatible with latest engine technology including vehicles fitted with exhaust after-treatment units that require an ACEA C5 grade
- Delivers the highest levels of fuel efficiency
 For use in new Jaguar and Land Rover vehicles
 that require a lubricant with the STJLR.51.5122
 specification and new Mercedes Benz vehicles
 requiring MB 229.71 specification.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 14-11-2018