



Typical Inspection Data:

Density @ 20 °C	1.035 g/cm ³
Viscosity @ 100 °C	2.2 cSt
Viscosity @ -40 °C	1250 cSt
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	245 °C
Wet Equilibrium Reflux Boiling Point	150 °C
pH (50% EtOH)	9.5

DOT 3

Synthetic Brake Fluid

Recommended by Comma for applications requiring:

FMVSS 116 DOT 3, ISO 4925 (Class 3), SAE J1703

Product Features:

- Standard Brake Fluid for older vehicles where a DOT 3 fluid is specified.
- Suitable for use in drum, disc, tandem brake & hydraulic clutch systems.
- Can be mixed safely with other fluids meeting FMVSS 116 DOT 3; ISO 4925 (Class 3); SAE J1703.

Directions for use:

1. IMPORTANT - Follow vehicle manufacturer's recommendations.
2. Keep Brake Fluid clean and dry.
3. Store in original container only.
4. Keep container clean and tightly closed to prevent water absorption.
5. Caution: Do not refill container and do not use for other liquids.
6. Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.
7. All brake fluids absorb moisture and therefore they must be checked or changed regularly.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

07-02-17