

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.847 g/cm ³
Viscosity @ 100°C	12.0 cSt
Viscosity @ 40°C	68 cSt
Viscosity Index	175
Viscosity CCS @ -30°C	5200 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Eco R 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

ACEA C3; Renault RN-17

Product Features:

- Fully synthetic, high performance 5W-30 engine oil. Suitable for modern petrol and diesel vehicles.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 20-11-2019