



Typical Inspection Data:

Density @ 20°C	1.074 g/cm ³
Appearance	Clear red liquid
Approx. protection	-36°C

Xstream® G30® Antifreeze & Coolant Ready Mixed

Glysantin® G30® Ready Mix by BASF is approved by:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW (TL774-D/F); DAF (MAT74002); Deutz (DQC CB-14); Jaguar vehicles built from 1999 (VIN 878389); MAN (MAN 324 SNF); Mercedes Benz (MB-Approval 326.3); Mini Cooper D from 2007-2010; MTU (MTL 5048); Porsche vehicles built between 1996 and 2009; Siemens (wind power).

Based on Coolant Concentrate that conforms to the requirements of BS 6580:2010

Product Features:

- Ready to use ethylene glycol based antifreeze & coolant with OAT inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

1. Do not dilute - pour directly into vehicle cooling system.
2. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
3. Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

13-07-2017