



Typical Inspection Data:

Density @ 20°C	0.856 g/cm ³
Viscosity @ 100°C	14.2 cSt
Viscosity @ 40°C	96 cSt
Viscosity Index	150
Viscosity CCS @ -25°C	6400 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	0.98%
Zinc	0.09%
Calcium	0.26%
Phosphorus	0.08%
Colour	Brown
Flash Point	200°C
Pour Point	-33°C

TransFlow UD 10W-40

Fully Synthetic

Recommended by Comma for applications requiring:

ACEA E6 E7

Volvo VDS-3; RVI RLD-2; MTU Type 3.1; MACK EO-N

Official Approvals:

TransFlow UD 10W-40 is officially approved by:

MAN 3477; MB-Approval 228.51

MAN renewal approval application submitted to the OEM. Certification process delayed by OEM due to Covid-19. Expected to be completed by March-2022.

Product Features:

- Fully synthetic, 10W-40 low SAPS oil, to protect both engine and emission control equipment.
- Suitable for high performance diesel engines including turbo charged and naturally aspirated.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 14-12-2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com