



### Typical Inspection Data:

Density @ 20°C	0.826 g/cm <sup>3</sup>
Viscosity @ 40°C	18.5 cSt
Viscosity @ -40°C	940 cSt
Colour	Orange
Flash Point	135°C
Pour Point	-54°C
Viscosity Index	340

## LDS Fluid

Suspension, Power Steering, & Hydraulic System Fluid

**Recommended by Comma for applications requiring:**

Suitable for certain Peugeot, Citroën, DS, Ssangyong & Toyota models that require PSA S71 2710.

### Product Features:

- LDS Fluid is a synthetic formulation that may be used in all applications that currently require PSA S71 2710 in certain Peugeot, Citroën, DS, Ssangyong & Toyota models.

### Directions for use:

- Always follow the vehicle manufacturer's recommendations when adding LDS Fluid.
- Check vehicle handbook if in doubt.
- This product is not compatible with rubber components designed for use with DOT Brake Fluids.
- Keep fluid clean.
- Caution: Store only in its original container. .
- Keep container clean and tightly closed.
- Do not refill container or use for other liquids.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

19-01-2017