



Typical Inspection Data:

| | |
|--------------------|-------------------------|
| Density @ 20 °C | 0.845 g/cm ³ |
| Viscosity @ 100 °C | 16.0 cSt |
| Viscosity @ 40 °C | 100 cSt |
| Calcium | 0.29 % |
| Phosphorus | 0.05 % |
| Colour | Brown |
| Pour Point | -39 °C |

Performance Profile:

Recommended by Comma for certain Ford, Vauxhall, Mazda, Volvo & VAG Group applications and generally where a 75W90, API GL4 oil is specified. Suitable for use where the following specifications are called for:

| | |
|--------------------------------------|---|
| Ford WSD-M2C200-C | Volvo 97309 |
| Ford WSD-M2C200-B | Volkswagen G 50 |
| GM 1940768 | API GL-4 (75W-85) |
| GM 1940182 | GM 1940764 |
| API GL-4 synthetic (75W-85 & 75W-90) | Special transmission oil, Castrol BOT 130 |

BMW MTF LT-4

MVMTF Plus 75W-90

Fully Synthetic

Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Good low temperature performance.
- Excellent cleanliness.
- Robust corrosion protection.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

30-11-2017