



Typical Inspection Data:

Density @ 20 °C	0.840 g/cm ³
Viscosity @ 100 °C	7.3 cSt
Viscosity @ 40 °C	36 cSt
Phosphorus	0.02%
Colour	Straw
Pour Point	-36 °C

Performance Profile:

Recommended by Comma for certain DSG and DCT transmissions.
Suitable for use where the following specifications are called for:

BMW Drivelogic 7-speed (Getrag) DCTF-1, BMW 6-Speed DCT, BMW MTF LT-5	Borg Warner
Bugatti Veyron	Castrol BOT 341
Chrysler 68044345 EA & GA, Powershift 6-speed Getrag	DCT-1
Ferrari 7-speed (Getrag)/TE DCT-3	Ford/Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A, Part # 1490763/1490761, WSS-M2C200-D2 / XT-11-QDC
Mitsubishi TC-SST 6-speed (GFT) / MZ320065 Dia Queen SSTF-1	Pentosin FFL 2, FFL 3, FFL 4
Peugeot/Citroen DCS 6-speed (GFT)/9734. S2	Renault EDC 6-speed (Getrag)
Shell TF DCT-F3	Volvo Powershift 6-speed (GFT) / 1161838/1161839
VW (Audi, Seat, Skoda) 6-speed, VW/Audi TL 52529 (spec) / G 052 529 A2 or A6 (fluid), VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid)	ZF/Porsche Oil #999.917.080.00
MB 236.21	

AQDCT PLUS

Fully Synthetic

Product Features:

- High performance DCT fluid for use in the widest range of vehicle makes fitted with DSG or DCT wet transmissions
- Provides excellent friction durability, scuffing protection and fatigue resistance
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

Pack Size Availability:

- 1L
- 5L
- 20L

UPDATED: 24/01/18

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.

Comma Oil & Chemicals Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com