



Typical Inspection Data:

Density @ 20°C	0.855 g/cm ³
Viscosity @ 100°C	7.0 cSt
Colour	Red

Fuel: Oil Mix Guide

Ratio	50:1	40:1	32:1	30:1	25:1	24:1	20:1	16:1
ml of oil required per litre of fuel	20	25	31	33	40	41	50	63

2 Stroke Sport

Recommended by Comma for applications requiring:

JASO FC/FD, ISO-L-EGB,
API TC, TISI

Product Features:

- Low ash semi-synthetic oil for two stroke petrol engines (motorcycles, mopeds, cars, chain saws, lawnmowers etc) requiring an oil of this type and quality level.
- Low smoke semi-synthetic formulation incorporating poly-iso-butylene (PIB) to ensure good lubricity.
- Excellent ring sticking and high temperature performance.
- Helps prevent spark plug whiskering and corrosion.
- May be diluted up to a 50:1 ratio – follow engine manufacturer's recommendations.

Important:

- The engine manufacturer's recommendations on mixture ratios should be observed.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 20-07-2018