



Typical Inspection Data:

Density @ 20°C	1.088 g/cm ³
Appearance	Clear violet liquid
Approx. Protection	-36°C

Xstream® GG40® Antifreeze & Coolant

Ready Mixed

Glystantin® GG40® by BASF is approved by:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW vehicles as from 2011 (TL 774-J). This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010.

Product Features:

- Ethylene glycol and glycerine based antifreeze with advanced silicate inhibitors (Si-OAT).
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

- Do not dilute - pour directly into vehicle cooling system.
- Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
- Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 05-07-2021