

Technical Data Sheet



Typical Inspection Data: Density @ 20 °C 0.848 g/cm³ Viscosity @ 100 °C 6.9 cSt Viscosity @ 40 °C 37 cSt Calcium 0.29% Phosphorus 0.05% Colour Brown Pour Point -39 °C

Performance Profile:

Recommended by Comma for certain BMW, Ford, Land Rover & VAG group applications and generally where a 75W, API GL-4 oil is specified. Suitable for use where the following specifications are called for:

BMW MTF LT-3; Ford WSS-M2C200-D2; GM 19259104 (BOT 303); VW G 052 178; VW G 060 726; VW G 052 171; VW G 052 726; VW G 052 512; VW G 070 726 A2; VW G 052 527 A2; Special transmission oil, BOT 350 M3; Fiat 9.55550-MZ6; PSA 9730 A8.

MVMTF Plus 75W

Fully Synthetic

Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Fuel-economy benefits due to low viscosity formulation.
- Exceptional cold temperature performance properties.
- High shear stability for long lasting fluid performance.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 13.01.2022

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com