COMMA®

Technical Data Sheet



AQCVT® PLUS

Fully Synthetic

Product Features:

- High performance CVT fluid for use in a wide range of vehicle makes, including Audi, Toyota, Ford, Mitsubishi, Mercedes Benz, Nissan and many more
- Provides excellent metal and clutch friction performance.
- Not suitable for Nissan, Toyota and Ford hybrid transmissions
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

Pack Size Availability:

- 1L

Typical Inspection Data:

Density @ 20 °C	0.845 g/cm3
Viscosity @ 100°C	7.5 cSt
Viscosity @ 40°C	36 cSt
Phosphorus	0.04%
Calcium	0.02%
Pour Point	-45°C

Performance Profile:

GM DEX-CVT, GM 1940713, GM 1940714	**Ford M2C928-A, WSS-M2C933-A, Mercon C**
Nissan NS-1 CVT fluid, Nissan NS-2 CVT fluid, Nissan NS-3 CVT fluid	**Mercedes Benz MB 236.20**
MG Rover Special ATF, EM-CVT	**Subaru Special ATF, Subaru CVT High Torque CVTF, Lineartronic CV-30, Lineartronic CVTF II, Special CVT fluid, Subaru iCVTF, NS-2**
BMW/Mini Cooper Special CVT fluid, Esso EZL-799 (ZF CVT V1)	**Honda Special CVT fluid Honda, Special CVTF fluid Honda, HCF-2; Hyundai/Kia CVT-J1, SP III (CVT model)**
Mazda Special CVT fluid, Mobil CVTF 3320	**Dodge/ Jeep Special CVT fluid, Mopar CVTF +4**
Toyota Special CVT fluid, Toyota CVT TC, Special CVT fluid, Toyota CVT FE	**Renault Special fluid Elf Matic CVT**
Suzuki CVT Fluid Green 1, Suzuki CVT Fluid Green 2, CVTF TC, CVTF 3320	**Audi/VW VW G 052 180/ TL 052 180, VW G 052 516/ TL 052 516, (VW G 055 190, VW G 052 190 Differential Oil)**
Idemitsu CVTS-EX1	**Daihatsu Ammix CVTF-DC, Ammix CVTF-DFC, Ammix CVTF-TC, Ammix CVTF-DFE**
Mitsubishi DiaQueen CVTF J1, DiaQueen CVTF J4, DiaQueen CVTF J4+	

UPDATED: 24/01/18

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.

Comma Oil & Chemicals Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com **www.CommaOil.com**

BRA2780/CB/UK