



## X-Flow Type V 5W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

VW 504 00, VW 507 00  
ACEA C3

### Product Features:

- Fully synthetic 5W-30 oil for VW/Audi group petrol and diesel vehicles including those operating under long life service regimes.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

### Typical Inspection Data:

Density @ 20 °C	0.848 g/cm <sup>3</sup>
Viscosity @ 100 °C	12.1 cSt
Viscosity @ 40 °C	70 cSt
Viscosity Index	170
Viscosity CCS @ -30 °C	6300 cP
T.B.N.	8.5 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

25-05-17