



## Typical Inspection Data:

Density @ 20°C	0.853 g/cm <sup>3</sup>
Viscosity @ 100°C	13.5 cSt
Viscosity @ 40°C	80 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point (Closed Cup)	210°C
Pour Point	-39°C

## Syner-G 5W-40

### Fully Synthetic

#### Official Approvals:

Approved under VW standard 502 00 and VW standard 505 00; MB-Approval 229.3

#### Recommended by Comma for applications requiring:

MB 226.5, MB 229.1; PSA B71 2296; RN0700, RN0710; BMW LL-01; PORSCHE A40; ACEA A3/B4; API SN CF

#### Product Features:

- Fully synthetic, high performance 5W-40 oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at [CommaOil.com](http://CommaOil.com).

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 22-02-2018