



## Typical Inspection Data:

Density @ 20°C	0.847 g/cm <sup>3</sup>
Viscosity @ 100°C	11.9 cSt
Viscosity @ 40°C	68 cSt
Viscosity Index	173
Viscosity CCS @ -30°C	5700 cP
T.B.N.	6.6 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.10%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

## X-Flow Type R 5W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

RN0720  
ACEA C4

### Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C4 grade.
- Do not mix this oil with other Types of oil, as therequirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight diget code printed on the bottle. YYYY.MM.DD.

UPDATED: 06/12/2018