COMMA

Technical Data Sheet



Eco-F 5W-20

Fully Synthetic

Recommended by Comma for applications requiring:

FORD WSS M2C948-B, WSS-M2C925-A, WSS-M2C925-B; Jaguar Land Rover STJLR.03.5004; ACEA C5; API SN

Product Features:

- Fully synthetic, high performance 5W-20 oil suitable for use in the latest Ford EcoBoost engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20 °C	0.847 g/cm^3
Viscosity @ 100 °C	8.0 cSt
Viscosity @ 40 °C	43 cSt
Viscosity Index	161
Viscosity CCS @ -30 °C	4300 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.09%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230 °C
Pour Point	-36 °C

12-09-2017

Comma Oil & Chemicals Ltd.
Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000
Email: sales@commaoil.com www.CommaOil.com