



## Typical Inspection Data:

Density @ 20 °C	0.840 g/cm <sup>3</sup>
Viscosity @ 100 °C	12.1 cSt
Viscosity @ 40 °C	61 cSt
Viscosity Index	200
Viscosity CCS @ -35 °C	5900 cP
T.B.N.	8.2 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Amber
Flash Point	>200°C
Pour Point	-48°C

## Eco-VG 0W-30

Fully Synthetic

**Recommended by Comma for applications requiring:**

VW 504 00, VW 507 00;  
Porsche C30;  
ACEA C3

### Product Features:

- Fully synthetic engine oil exceeding 5W-30 VW 504/507 fuel efficiency requirements by over 25%.
- Designed to contain low SAPS for enhanced CAT and DPF protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at [www.CommaOil.com](http://www.CommaOil.com).

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

28-12-2016